

90° ANGLED TUBE CABLE LUG



Illustration only

Standard (similar to DIN)

Application area

For multi-wire round conductors, such as compliant with DIN EN 60228 Class 2 for round-pressed sector cables

Notice

The fitter must check the inserted cable (by trying to pull it out if necessary).

Max. temperature resistance	125 °C
Material	Electrolytic copper
Surface	Tin-plated

Wire cross section	Flange hole	Wire diameter (d1)	Diameter of hole (d2)	Sleeve length (a)	Width (b)	Art. No.	P. Qty.
10 mm ²	M5	4.5 mm	5.3 mm	10.0 mm	12.0 mm	5633 210 5	100
10 mm ²	M6	4.5 mm	6.4 mm	10.0 mm	12.0 mm	5633 210 6	100
10 mm ²	M8	4.5 mm	8.4 mm	10.0 mm	15.0 mm	5633 210 8	100
10 mm ²	M10	4.5 mm	10.5 mm	10.0 mm	17.0 mm	5633 210 10	100
16 mm ²	M5	5.5 mm	5.3 mm	13.0 mm	12.0 mm	5633 216 5	100
16 mm ²	M6	5.5 mm	6.4 mm	13.0 mm	12.0 mm	5633 216 6	100
16 mm ²	M8	5.5 mm	8.4 mm	13.0 mm	15.0 mm	5633 216 8	100
16 mm ²	M10	5.5 mm	10.5 mm	13.0 mm	17.0 mm	5633 216 10	100
25 mm ²	M5	7 mm	5.3 mm	15.0 mm	14.0 mm	5633 225 5	100
25 mm ²	M6	7 mm	6.4 mm	15.0 mm	14.0 mm	5633 225 6	100
25 mm ²	M8	7 mm	8.4 mm	15.0 mm	16.0 mm	5633 225 8	100
25 mm ²	M10	7 mm	10.5 mm	15.0 mm	18.0 mm	5633 225 10	100
35 mm ²	M6	8.5 mm	6.4 mm	17.0 mm	17.0 mm	5633 235 6	50
35 mm ²	M8	8.5 mm	8.4 mm	17.0 mm	17.0 mm	5633 235 8	50
35 mm ²	M10	8.5 mm	10.5 mm	17.0 mm	19.0 mm	5633 235 10	50
35 mm ²	M12	8.5 mm	13.2 mm	17.0 mm	21.0 mm	5633 235 12	50
50 mm ²	M6	10.0 mm	6.4 mm	19.0 mm	20.0 mm	5633 250 6	50
50 mm ²	M8	10.0 mm	8.4 mm	19.0 mm	20.0 mm	5633 250 8	50
50 mm ²	M10	10.0 mm	10.5 mm	19.0 mm	20.0 mm	5633 250 10	50
50 mm ²	M12	10.0 mm	13.2 mm	19.0 mm	23.0 mm	5633 250 12	50
70 mm ²	M8	12.0 mm	8.4 mm	21.0 mm	24.0 mm	5633 270 8	25
70 mm ²	M10	12.0 mm	10.5 mm	21.0 mm	24.0 mm	5633 270 10	25
70 mm ²	M12	12.0 mm	13.2 mm	21.0 mm	24.0 mm	5633 270 12	25
95 mm ²	M8	13.5 mm	8.4 mm	25.0 mm	26.0 mm	5633 295 8	25
95 mm ²	M10	13.5 mm	10.5 mm	25.0 mm	26.0 mm	5633 295 10	25
95 mm ²	M12	13.5 mm	13.2 mm	25.0 mm	26.0 mm	5633 295 12	25
120 mm ²	M8	15.0 mm	8.4 mm	26.0 mm	28.0 mm	5633 212 08	25
120 mm ²	M10	15.0 mm	10.5 mm	26.0 mm	28.0 mm	5633 212 010	25
120 mm ²	M12	15.0 mm	13.2 mm	26.0 mm	28.0 mm	5633 212 012	25
150 mm ²	M10	16.5 mm	10.5 mm	30.0 mm	31.0 mm	5633 215 010	25
150 mm ²	M12	16.5 mm	13.2 mm	30.0 mm	31.0 mm	5633 215 012	25
185 mm ²	M10	19.0 mm	10.5 mm	32.0 mm	35.0 mm	5633 218 510	25
185 mm ²	M12	19.0 mm	13.2 mm	32.0 mm	35.0 mm	5633 218 512	25
240 mm ²	M10	21.0 mm	10.5 mm	35.0 mm	39.0 mm	5633 224 010	25
240 mm ²	M12	21.0 mm	13.2 mm	35.0 mm	39.0 mm	5633 224 012	25

Can be stored in ORSY® system