

SET SCREWS

DIN EN ISO 4029

replaces DIN 916

with Allen socket and
up point

A2 stainless steel, 21 H
A4 stainless steel, 21 H



Hardness 21H corresponds to a hardness of
210 HV.

Nominal dia. d	Length l in mm	A2 stainless steel Art. No.	P. Qty.	A4 stainless steel Art. No.	P. Qty.
M5	5	0244 5 5	200	0269 95 5	200
	6	0244 5 6		0269 95 6	
	8	0244 5 8		0269 95 8	
	10	0244 5 10		0269 95 10	
	12	0244 5 12		0269 95 12	
	16	0244 5 16		0269 95 16	
	20	0244 5 20		0269 95 20	
	25	0244 5 25		0269 95 25	
	30	0244 5 30		0269 95 30	
	35	0244 5 35			
	40	0244 5 40			
	50	0244 5 50			
	60	0244 5 60			
M6	5	0244 6 5	100		100
	6	0244 6 6		0269 96 6	
	8	0244 6 8		0269 96 8	
	10	0244 6 10		0269 96 10	
	12	0244 6 12		0269 96 12	
	16	0244 6 16		0269 96 16	
	20	0244 6 20		0269 96 20	
	25	0244 6 25		0269 96 25	
	30	0244 6 30		0269 96 30	
	35	0244 6 35		0269 96 35	
	40	0244 6 40		0269 96 40	
	45	0244 6 45			
	50	0244 6 50		0269 96 50	
	55	0244 6 55			
	60	0244 6 60			
M8	6	0244 8 6	100	0269 98 6	100
	8	0244 8 8		0269 98 8	
	10	0244 8 10		0269 98 10	
	12	0244 8 12		0269 98 12	
	14	0244 8 14			
	16	0244 8 16		0269 98 16	
	20	0244 8 20		0269 98 20	
	25	0244 8 25		0269 98 25	
	30	0244 8 30		0269 98 30	
	35	0244 8 35		0269 98 35	
	40	0244 8 40		0269 98 40	
	45	0244 8 45		0269 98 45	
	50	0244 8 50		0269 98 50	
	60	0244 8 60		0269 98 60	
	70	0244 8 70			

Can be stored in ORSY®

DIN 916 has been retracted
and replaced by international
standard DIN EN ISO 4029.