



# Bristle Disk

High-performance cleaning disk suitable for universal use on pneumatic rod grinders (angled down), flexible shafts and 115 mm pneumatic or electric angle grinders (with 75 mm dia. in conjunction with M 14 holder).

## Applications:

- Removing tough, thick and thin coatings, such as paint, rust, lime, adhesive bonding points, gasket residues, coatings or soiling on all types of metal, cleaning concrete, natural stone, wood and plastics.

Dia. mm	Mounting system	Max. rpm	Color	Grain	Art. No.	P. Qty.
50	Compatible with 3M Roloc System	25,000	purple	36	<b>0673 000 503</b>	10
			green	50	<b>0673 000 505</b>	
			yellow	80	<b>0673 000 508</b>	
			white	120	<b>0673 000 501</b>	
75		18,000	green	50	<b>0673 000 755</b>	5
			yellow	80	<b>0673 000 758</b>	
			white	120	<b>0673 000 751</b>	
115	M 14 thread for angle grinder	12,000	green	50	<b>0673 001 155</b>	
			yellow	80	<b>0673 001 158</b>	
			white	120	<b>0673 001 151</b>	

## Holder

Design	Tot. length mm	Art. No.	P. Qty.
6 mm shank, for 50 mm dia. disks	50	<b>0586 673 02</b>	
6 mm shank, for 75 mm dia. disks		<b>0586 673 03</b>	1
M14 thread, for 75 mm dia. disks	35	<b>0586 673 04</b>	

## Version

- Cast from a single piece.

**Your advantages:**

No bristle come loose.  
No danger of injury.  
Controlled, low-noise operation.

- Unique tough "CUBITRON" (ceramic abrasive grain).

**Your advantage:**

High cutting capacity, aggressive and extremely high service life without high contact pressure.

- Suitable for up 25,000 rpm.

**Your advantage:**

Can be used on virtually all hand-guided machines.

- High, uniform degree of use up to complete consumption of entire disk.

**Your advantage:**

Cost savings.

- Toolless quick-change mounting system for 50 mm and 75 mm dia.

**Your advantages:**

Quick, easy mounting.  
Low equipping costs.

- Integrated M14 thread with 115 mm dia.

**Your advantage:**

No special support plate required.  
Cost savings.

