

PLASTIC CABLE DRUM



- Drum housing made of special plastic
- Generously dimensioned, swivelling rotary crank handle
- Innovative plug mounting
- Locking brake with „Open/Close switch“
- Made in Germany

Art. No.	0774 100 000
P. Qty.	1
Cable type	Unpopulated (only designed for 1.5 mm ²)
Version	3 grounding-contact sockets, 16 A, 250 V
IP protection class	Dependent on the cable installed
Protection class	Protection class I/protective grounding
Width	210 mm
Height	395 mm
Nominal voltage	250

Application area

Range of application depends on type of cable supplied

Notice

Thermal circuit-breaker with trip-free mechanism, resettable by hand after cooling.

PLASTIC CABLE DRUM 250 V



K2 in line with BGI 600

- Drum housing made of special plastic
- Generously dimensioned, swivelling rotary crank handle
- Innovative plug mounting
- Locking brake with „Open/Close switch“
- RN cable approved for use in difficult construction conditions in line with VDE 0100 Part 704
- Made in Germany

Proof of Performance

- Complies with BGI 608
- Tested according to EN standard 61242

Art. No.	0774 125 315	0774 140 315
P. Qty.	1	1
Cable length	25 m	40 m
Cable type	H07RN-F3G1.5 mm ²	H07RN-F3G1.5 mm ²
Version	3 grounding-contact sockets, 16 A, 250 V	3 grounding-contact sockets, 16 A, 250 V
IP protection class	IP X4	IP X4
Protection class	Protection class I/protective grounding	Protection class I/protective grounding
Width	210 mm	210 mm
Height	395 mm	395 mm
Nominal voltage	250	250

Application area

The industrial/construction site cable drum is suitable for use on construction sites and outdoors.

Notice

Thermal circuit breaker with trip-free mechanism, resettable by hand after cooling.