

SCREWDRIVER



Electronic screwdriver for use with wood, metal and sheet-metal screws. Complete in metal carrying case including universal holder and 6 bits.

S 15 Ergo
Art. No. 0702 150 1

- Electronic speed control.
- Lock button for continuous operation.
- Adjustable claw clutch for torque pre-selection.
- Torque can also be controlled via contact pressure.
- Screw depth adjustable via depth stop in 1/4 mm steps.
- Stable polyamid motor case with aluminium backing and metal gear head for most demanding applications.
- Ergonomic handle with two holding positions for sensitive screwing and secure grip.
- Short, compact design.
- Standard tool mount (7 mm with tang) for optimum centring and power transmission.
- Switchable left-right.
- Quality product made in Germany.
- 3 year warranty

Delivery scope		
Designation	Art. No.	P. Qty.
Screwdriver S 15 Ergo	-	1
Metal carrying case with small-parts compartment, foam liner	0955 702 310	1
Universal holder 7 mm with quick-change chuck for 1/4" bits	0614 176 710	1
Bit 1/4" PH1 , length 25 mm	0614 176 274	1
Bit 1/4" PH2 , length 25 mm	0614 176 461	1
Bit 1/4" PH3 , length 25 mm	0614 176 648	1
Bit 1/4" PZ 1 , length 25 mm	0614 176 651	1
Bit 1/4" PZ 2 , length 25 mm	0614 176 652	1
Bit 1/4" PZ 3 , length 25 mm	0614 176 653	1
Hexagon offset screwdriver SW 2	0715 31 36	1

Available separately	
Designation	Art. No.
Carbon brushes, individual	0708 130 007

Applications	
Screw type	dia. in mm
Wood and chipboard screws	3,0 - 6,0
Sheet-metal screws	3,5 - 6,3
Metric screws/nuts	M4 - M6
Thread-cutting screws	3,0 - 6,0
Locking screws	3,0 - 6,0

Technical Data										
Voltage	Protection class	Idling speed	Load speed	Power consumption	Power output	Tool mounting	Maximum torque for hard screwing instance Nm	Length connection cord	Width across corners in mm	Weight
		rpm	rpm	Watt	Watt	①		in m	in mm	in kg
230 V / 50 Hz	□ / II	0-800	0-450	230	125	7 mm with tang (H 7 acc. to DIN 3126)	approx. 12	5	23	appr. 1.6

Accessories		
Designation	Art. No.	P. Qty.
Bit 7 mm Phillips , length 53 mm	0614 176 74.	1
Bit 7 mm Pozidriv , length 53 mm	0614 176 66.	1
Slot bits 7 mm , length 53 mm	0614 177 9..	1
AW bits 7 mm , length 53 mm	0614 53 ...	1
Adapter 7 mm for 1/4" socket spanner, length 50 mm	0614 923 131	1
Hexagon socket spanner inserts 1/4", 5.5 mm	0713 111 155	1
Hexagon socket spanner inserts 1/4", 7.0 mm	0713 111 107	1
Hexagon socket spanner inserts 1/4", 8.0 mm	0713 111 108	1
Hexagon socket spanner inserts 1/4", 10.0 mm	0713 111 110	1
Hexagon socket spanner inserts 1/4", 12.0 mm	0713 111 112	1
Hexagon socket spanner inserts 1/4", 13.0 mm	0713 111 113	1

Please take note of the depth-stop accessories S 13 and S 15.

