

CONCRETE PLIERS

DIN 5242



Art. No.	0715 02 04	0715 02 05	0715 02 06	0715 02 07
P.	1	1	1	1
Length	200 mm	220 mm	250 mm	280 mm
Length in inches	5 in	8 1/2 in	10 in	11 in
Type	Polished head	Polished head	Polished head	Polished head
Surface	Phosphated	Phosphated	Phosphated	Phosphated

PINCERS

DIN 5241, German shape



Art. No.	0715 02 01	0715 02 02	0715 02 03
P.	1	1	1
Length	180 mm	210 mm	250 mm
Length in inches	7 in	8 in	10 in
Type	Polished head	Polished head	Polished head
Surface	Phosphated	Phosphated	Phosphated

HIGH-LEVERAGE CONCRETE PLIERS / MECHAN-



Similar to illustration

Art. No.	0715 02 10	0715 02 101
P.	1	1
Length	300 mm	300 mm
Length in inches	12 in	12 in
Type	Polished head	
Surface	Phosphated	Nickel-plated

Cutting shock dampened after cutting through the binding wire
Relieves the musculature and tendons

High force transmission ratio
Ideal cutting performance with minimal application of force

Twisted binding wire of 2 x 2 mm dia. is cut effortlessly, as is soft wire up to 5 mm dia.

Also for working in hard-to-reach areas
Slimline design

Application

Use in building construction, steel construction and civil engineering: Manufacturing of prefabricated concrete parts