

RING-SHAPED CRIMP CABLE LUG

DIN 46234 and similar

Min./max. wire cross section	Wire cross section	Flange hole	Nominal size	Wire diameter (d1)	Diameter of hole (d2)	Distance between sleeve end and centre of hole (l)	Sleeve length	Width (b)	Art. No.	P. Qty.
	25 mm ²	M10	10 - 25	7.5 mm	10.5 mm	26 mm	11 mm	18 mm	0967 625 10	50
	25 mm ²	M12	12 - 25	7.5 mm	13.0 mm	31 mm	11 mm	22 mm	0967 625 12	50
	35 mm ²	M6	6 - 35	9.0 mm	6.5 mm	26 mm	12 mm	15 mm	0967 635 6	50
	35 mm ²	M8	8 - 35	9.0 mm	8.4 mm	26 mm	12 mm	16 mm	0967 635 8	50
	35 mm ²	M10	10 - 35	9.0 mm	10.5 mm	27 mm	12 mm	18 mm	0967 635 10	50
	35 mm ²	M12	12 - 35	9.0 mm	13.0 mm	31 mm	12 mm	22 mm	0967 635 12	50
	50 mm ²	M6	6 - 50	11.0 mm	6.5 mm	34 mm	16 mm	18 mm	0967 650 6	50
	50 mm ²	M8	8 - 50	11.0 mm	8.4 mm	34 mm	16 mm	18 mm	0967 650 8	50
	50 mm ²	M10	10 - 50	11.0 mm	10.5 mm	34 mm	16 mm	18 mm	0967 650 10	50
	50 mm ²	M12	12 - 50	11.0 mm	13.0 mm	36 mm	16 mm	22 mm	0967 650 12	50
	50 mm ²	M16	16 - 50	11.0 mm	17.0 mm	40 mm	16 mm	28 mm	0967 650 16	50
	70 mm ²	M6	6 - 70	13 mm	6.5 mm	38 mm	18 mm	22 mm	0967 670 6	25
	70 mm ²	M8	8 - 70	13.0 mm	8.4 mm	38 mm	18 mm	22 mm	0967 670 8	25
	70 mm ²	M10	10 - 70	13.0 mm	10.5 mm	38 mm	18 mm	22 mm	0967 670 10	25
	70 mm ²	M12	12 - 70	13.0 mm	13.0 mm	38 mm	18 mm	22 mm	0967 670 12	25
	70 mm ²	M16	16 - 70	13.0 mm	17.0 mm	42 mm	18 mm	28 mm	0967 670 16	25
	95 mm ²	M8	8 - 95	15 mm	8.4 mm	42 mm	20 mm	24 mm	0967 695 8	25
	95 mm ²	M10	10 - 95	15.0 mm	10.5 mm	42 mm	20 mm	24 mm	0967 695 10	25
	95 mm ²	M12	12 - 95	15.0 mm	13.0 mm	42 mm	20 mm	24 mm	0967 695 12	25
	95 mm ²	M16	16 - 95	15.0 mm	17.0 mm	44 mm	20 mm	28 mm	0967 695 16	25
	120 mm ²	M8	8 - 120	16.5 mm	8.4 mm	44 mm	22 mm	24 mm	0967 612 08	25
	120 mm ²	M10	10 - 120	16.5 mm	10.5 mm	44 mm	22 mm	24 mm	0967 612 010	25
	120 mm ²	M12	12 - 120	16.5 mm	13.0 mm	44 mm	22 mm	24 mm	0967 612 012	25
	120 mm ²	M16	16 - 120	16.5 mm	17.0 mm	48 mm	22 mm	28 mm	0967 612 016	25
	150 mm ²	M10	10 - 150	19.0 mm	10.5 mm	50 mm	24 mm	30 mm	0967 615 010	10
	150 mm ²	M12	12 - 150	19.0 mm	13.0 mm	50 mm	24 mm	30 mm	0967 615 012	10
	150 mm ²	M16	16 - 150	19.0 mm	17.0 mm	50 mm	24 mm	30 mm	0967 615 016	10
	185 mm ²	M10	10 - 185	21 mm	10.5 mm	50 mm	28 mm	36 mm	0967 618 510	10
	185 mm ²	M12	12 - 185	21.0 mm	13.0 mm	50 mm	28 mm	36 mm	0967 618 512	10
	185 mm ²	M16	16 - 185	21.0 mm	17.0 mm	50 mm	28 mm	36 mm	0967 618 516	10
	240 mm ²	M12	12 - 240	23.5 mm	13.0 mm	56 mm	32 mm	38 mm	0967 624 012	10
	240 mm ²	M16	16 - 240	23.5 mm	17.0 mm	56 mm	32 mm	38 mm	0967 624 016	10

Can be stored in ORSY system