

Pneumatic impact screwdriver DSS 1/2 inch Premium COMPACT

High-quality impact screwdriver in robust, fibre-glass-reinforced plastic housing, with above-average performance values and convenient equipment features

- Excellent power-to-weight ratio
- Up to 1100 Nm max. breakaway torque with a weight of just 1.1 kg
- Reliable maximum performance values and a long service life
- High-quality hammer impact mechanism and cylinder with unique 7-disc motor
- 4-step power setting with convenient one-hand reversing always ensures optimum, user-friendly adjustment for the relevant application
- Excellent handling and optimal control
- Particularly ergonomic handle with soft grip components and precise trigger



2 Years WÜRTH MASTERPLUS Warranty for wear damage

The current WÜRTH MASTERPLUS warranty conditions must be observed.

3 Years Warranty on manufacturing and material defects

Excluded are damages caused by improper use, overloading or failure to observe the operating instructions.

Type description	DSS 1/2 INCH PREMIUM COMPACT
Tool holding device	1/2-inch external square
Max. working torque	750 Nm
Max. releasing torque	1100 Nm
Sound-pressure level	88.6 dB
Vibration	7.88 m/s ²
Operating pressure	6.3 bar
Weight of machine	1.1 kg
Min. hose inner diameter	8 mm
Air consumption	135 l/min
Connection thread	G 1/4 inch
Length x width x height	115 x 61 x 186 mm

Art. no. 5714 308 0

P. Qty.: 1

Details/Application



Notice

- Recommended maximum bolt size: M14
- Impact screwdrivers are not torque screwdrivers. Connections requiring a specific torque must be checked by means of a torque measuring device after tightening with the impact screwdriver.
- When the impact screwdriver is used regularly, a little oil should be added daily via the air inlet, and approximately 2 strokes of gear grease should be added monthly via the grease nipple.
- Plug-in nipple not included in the scope of delivery

Related products	Art. no.
Plug-in nipple S2000AG	0699 100 614