

SET SCREWS

DIN EN ISO 4026

replaces DIN 913

with Allen socket and truncated cone

Bare steel, 45 H
Galvanized steel, blue passivated (A2K), 45 H

Hardness 45H corresponds to a hardness of 450 HV.

Nominal dia.	Length l in mm	Bare steel Art. No.	P. Qty.	Galvanized steel Blue-passivated Art. No.	P. Qty.
M12	20	0255 12 20	100	0255 012 20	100
	25	0255 12 25		0255 012 25	
	30	0255 12 30		0255 012 30	
	35	0255 12 35		0255 012 35	
	40	0255 12 40		0255 012 40	
	45	0255 12 45		0255 012 45	
	50	0255 12 50		0255 012 50	
	55	0255 12 55		0255 012 55	
	60	0255 12 60		0255 012 60	
	65	0255 12 65		0255 012 65	
	70	0255 12 70	50	0255 012 70	50
	80	0255 12 80		0255 012 80	
	90	0255 12 90		0255 012 90	
	100	0255 12 100		0255 012 100	
	110	0255 12 110			
	120	0255 12 120	10	0255 012 120	10
M16	10	0255 16 10	100		
	12	0255 16 12			
	14	0255 16 14			
	16	0255 16 16		0255 016 16	200
	20	0255 16 20	25	0255 016 20	
	25	0255 16 25		0255 016 25	
	30	0255 16 30		0255 016 30	
	35	0255 16 35		0255 016 35	100
	40	0255 16 40		0255 016 40	
	45	0255 16 45		0255 016 45	
	50	0255 16 50	10	0255 016 50	50
	55	0255 16 55		0255 016 55	
	60	0255 16 60		0255 016 60	
	65			0255 016 65	
	70	0255 16 70		0255 016 70	
	75			0255 016 75	
	80	0255 16 80		0255 016 80	
	90	0255 16 90		0255 016 90	
	95			0255 016 95	
	100	0255 16 100		0255 016 100	
	110	0255 16 110		0255 016 110	25
	120	0255 16 120		0255 016 120	
	130	0255 16 130			

Can be stored in ORSY®

DIN 913 has been retracted and replaced by international standard DIN EN ISO 4026.