

SET SCREWS

DIN EN ISO 4029

Nominal dia. d	Length l in mm	A2 stainless steel Art. No.	P. Qty.	A4 stainless steel Art. No.	P. Qty.
M10	8	0244 10 8	100		100
	10	0244 10 10		0269 910 10	
	12	0244 10 12		0269 910 12	
	16	0244 10 16		0269 910 16	
	20	0244 10 20		0269 910 20	
	25	0244 10 25		0269 910 25	
	30	0244 10 30		0269 910 30	
	35	0244 10 35		0269 910 35	
	40	0244 10 40		0269 910 40	
	45	0244 10 45			
	50	0244 10 50		0269 910 50	
	60	0244 10 60		0269 910 60	
	70	0244 10 70			
	80	0244 10 80			
M12	10	0244 12 10	100		50
	12	0244 12 12		0269 912 12	
	16	0244 12 16		0269 912 16	
	20	0244 12 20		0269 912 20	
	25	0244 12 25		0269 912 25	
	30	0244 12 30		0269 912 30	
	35	0244 12 35		0269 912 35	
	40	0244 12 40		0269 912 40	
	50	0244 12 50		0269 912 50	
	60	0244 12 60			
	70	0244 12 70			
M16	80	0244 12 80	50		
	90	0244 12 90			
	16	0244 16 16	50		
	20	0244 16 20			
	25	0244 16 25			
	30	0244 16 30			
	35	0244 16 35			
	40	0244 16 40			
	45	0244 16 45			
	50	0244 16 50			
	60	0244 16 60			
	70	0244 16 70			
	80	0244 16 80			
	90	0244 16 90			

Can be stored in ORSY®

replaces DIN 916

with Allen socket and cup point

A2 stainless steel, 21 H
A4 stainless steel, 21 H



Hardness 21H corresponds to a hardness of 210 HV.

DIN 916 has been retracted and replaced by international standard DIN EN ISO 4029.