

HEAT-SHRINK CABLE CONNECTOR HIGH-END PUSH CONNECTOR



Illustration only

Art. No.	0555 612 100	0555 612 200	0555 612 400
P. Qty.	50	50	50
Min./max. wire cross section	0.5-1.5 mm ²	1.5-2.5 mm ²	4-6 mm ²
Colour	Red	Blue	Yellow
Nominal size of flat plug/push connector/ blade connector	6.3 x 0.8 mm	6.3 x 0.8 mm	6.3 x 0.8 mm
Dielectric strength	30 kV/mm	30 kV/mm	30 kV/mm
IP protection class	IP 67	IP 67	IP 67
Min./max. temperature conditions	-55 to 125 °C	-55 to 125 °C	-55 to 125 °C
Min. shrinkage temperature	300 °C	300 °C	300 °C

Can be stored in ORSY

Crystal Clear™ heat-shrink tubing for optimum visual monitoring of the connection.

40% faster shrinking behaviour

Time-saving

Low shrinking temperature of +90 °C

Low risk of damage to connector and cable insulation

Notice

Avoid localised overheating of the heat-shrink tubing.

Proof of Performance

RoHS-compliant

Application area

Dust-proof and damp-proof connections. Good to excellent resistance against petrol, battery acid, diesel, engine oil, anti-freeze, brake fluid, 5% saline solution, isopropyl alcohol.

HEAT-SHRINK CABLE CONNECTOR HIGH-END BLADE CONNECTOR



Illustration only

Art. No.	0555 612 110	0555 612 210	0555 612 410
P. Qty.	50	50	50
Min./max. wire cross section	0.5-1.5 mm ²	1.5-2.5 mm ²	4-6 mm ²
Colour	Red	Blue	Yellow
Nominal size of flat plug/push connector/ blade connector	6.3 x 0.8 mm	6.3 x 0.8 mm	6.3 x 0.8 mm
Dielectric strength	30 kV/mm	30 kV/mm	30 kV/mm
IP protection class	IP 67	IP 67	IP 67
Min./max. temperature conditions	-55 to 125 °C	-55 to 125 °C	-55 to 125 °C
Min. shrinkage temperature	300 °C	300 °C	300 °C

Can be stored in ORSY

Crystal Clear™ heat-shrink tubing for optimum visual monitoring of the connection.

40% faster shrinking behaviour

Time-saving

Low shrinking temperature of +90 °C

Low risk of damage to connector and cable insulation

Notice

Avoid localised overheating of the heat-shrink tubing.

Proof of Performance

RoHS-compliant

Application area

Dust-proof and damp-proof connections. Good to excellent resistance against petrol, battery acid, diesel, engine oil, anti-freeze, brake fluid, 5% saline solution, isopropyl alcohol.