

HEAT-SHRINK CABLE CONNECTOR HIGH-END BUTT CONNECTOR



Illustration only

Dielectric strength	30 kV/mm
IP protection class	IP 67
Min./max. temperature conditions	-55 to 125 °C
Min. shrinkage temperature	300 °C

Art. No.	0555 610 1	0555 610 2	0555 610 4
P. Qty.	50 / 100	50 / 100	25 / 100
Min./max. wire cross section	0.5-1.5 mm ²	1.5-2.5 mm ²	4-6 mm ²
Colour	Red	Blue	Yellow
Length	38 mm	38 mm	41 mm

Can be stored in ORSY

Connection sleeve with inspection holes, Crystal Clear™ heat-shrink tubing for optimum visual monitoring of the connection.

40% faster shrinking process

Saves time

Low shrinking temperature of +300 °C

Low risk of damage to connector and cable insulation

Notice

Avoid localised overheating of the heat-shrink tubing.

Proof of Performance

RoHS-compliant

HEAT-SHRINK CABLE CONNECTOR HIGH-END RING CONNECTOR



Illustration only

Dielectric strength	30 kV/mm
IP protection class	IP 67
Min./max. temperature conditions	-55 to 125 °C
Min. shrinkage temperature	300 °C

Min./max. wire cross section	Colour	Flange hole	Art. No.	P. Qty.
0.5-1.5 mm ²	Red	M4	0555 611 104	50
0.5-1.5 mm ²	Red	M5	0555 611 105	50
1.5-2.5 mm ²	Blue	M4	0555 611 204	50
1.5-2.5 mm ²	Blue	M5	0555 611 205	50
1.5-2.5 mm ²	Blue	M6	0555 611 206	50
1.5-2.5 mm ²	Blue	M8	0555 611 208	50
1.5-2.5 mm ²	Blue	M10	0555 611 210	50
4-6 mm ²	Yellow	M4	0555 611 404	50
4-6 mm ²	Yellow	M5	0555 611 405	50
4-6 mm ²	Yellow	M6	0555 611 406	50
4-6 mm ²	Yellow	M8	0555 611 408	50
4-6 mm ²	Yellow	M10	0555 611 410	50

Can be stored in ORSY

Ring connector with inspection hole, Crystal Clear™ heat-shrink tubing for optimum visual monitoring of the connection.

Long-necked design

No impairment of contacts by the heat-shrink tubing

40% faster shrinking process

Saves time

Low shrinking temperature of +300 °C

Low risk of damage to connector and cable insulation

Notice

Avoid localised overheating of the heat-shrink tubing.

Proof of Performance

RoHS-compliant