

CONCRETE SCREW WIT

23.3

Concrete screw W-BS/A4, stainless steel A4 with hexagon head and pressed-on washer



Anchor size	Fastening height (variable) [mm]		Total length L [mm]	Effective embedment depth (variable) [mm]		Drill bit nominal dia. d_0 [mm]	Drill hole depth [mm]		Art. no.	PU/qty.	
	$t_{fix, max.}$	$t_{fix, min.}$		$h_{ef, min.}$	$h_{ef, max.}$		$h_{1, min.} \geq$	$h_{1, max.} \geq$			
10	10	5	90	80	85	10	90	95	5929 221 035	25	
	20	5	100		95			105			5929 221 045
	40	10	120		110			120			5929 221 065

Concrete screw W-BS/A4, stainless steel A4 with countersunk head



Anchor size	Fastening height (variable) [mm]		Total length L [mm]	Effective embedment depth (variable) [mm]		Drill bit nominal dia. d_0 [mm]	Drill hole depth [mm]		Art. no.	PU/qty.
	$t_{fix, max.}$	$t_{fix, min.}$		$h_{ef, min.}$	$h_{ef, max.}$		$h_{1, min.} \geq$	$h_{1, max.} \geq$		
10	10	5	90	80	85	10	90	95	5929 231 035	25

Concrete screw W-BS/A4, stainless steel A4 hanger bolt



Anchor size	Fastening height [mm]		Total length L [mm]	Effective embedment depth (variable) [mm]		Drill bit nominal dia. d_0 [mm]	Drill hole depth [mm]		Art. no.	PU/qty.
	$t_{fix, max.}$	$t_{fix, min.}$		$h_{ef, min.}$	$h_{ef, max.}$		$h_{1, min.} \geq$	$h_{1, max.} \geq$		
10	35	5	140	80	110	10	90	120	5929 261 060	25
	55	25	160					5929 261 080		

Cleaning accessories



For size	Nominal drill bit dia. d_0 [mm]	Cleaning brush (connecting thread M8) Art. no. PU [Qty.] = 1	Extension 2 x 345 mm (M8 connecting thread) Art. no. PU [Qty.] = 1	Handle Art. no. PU [Qty.] = 1	Machine mounting M8 female thread Art. no. PU [Qty.] = 1	Blow-out pump Art. no. PU [Qty.] = 1
10	10	0903 489 510	0903 489 111	0903 489 103	M8 and SDS plus: 0903 489 101	0903 990 001
12	12	0903 489 512				
14	14	0903 489 514				

Tangential impact screwdriver recommendation for installation

Size	Power tool	 1 2 3	Art. no.
10 and 12	ASS 18-A EC Combi	3	5700 510...
14	ASS 18 1/2" HT	-	0700 725 4