

## CABLE GLAND

Metric EN 60423

<b>Material</b>	<b>Polyamide PA6 V-2</b> , halogen and silicone-free
Sealing ring	Polychloroprene nitrile rubber CR/NBR, halogenic
Temperature range	-20°C to +100°C
Protection rating	IP68 - 5 bar
Colour	Light grey RAL 7035



	Connection thread	Cable dia. mm (clamping range)	Thread length mm	Width across flats mm	Art. no.	PU/Qty.
	M12 x 1.5	3-6	8	15	<b>0967 705 012</b>	100
	M16 x 1.5	5-10		20	<b>0967 705 016</b>	
	M20 x 1.5	8-13		24	<b>0967 705 020</b>	
	M25 x 1.5	11-17		29	<b>0967 705 025</b>	
	M32 x 1.5	15-21	10	36	<b>0967 705 032</b>	25
	M40 x 1.5	19-28		46	<b>0967 705 040</b>	10
	M50 x 1.5	27-35	12	55	<b>0967 705 050</b>	5
	M63 x 1.5	32-42		68	<b>0967 705 063</b>	

Can be stored in ORSY® system

## COUNTER NUT

Metric EN 60423

<b>Material</b>	<b>Polyamide PA6 GF30</b> , halogen and silicone-free
Temperature range	-20°C to +100°C
Colour	Light grey RAL 7035

	Connection thread	Thread length mm	Width across flats mm	Art. no.	PU/Qty.
	M12 x 1.5	5	17	<b>0967 710 12</b>	100
	M16 x 1.5		22	<b>0967 710 16</b>	
	M20 x 1.5	6	27	<b>0967 710 20</b>	
	M25 x 1.5		32	<b>0967 710 25</b>	
	M32 x 1.5	7	41	<b>0967 710 32</b>	50
	M40 x 1.5		50	<b>0967 710 40</b>	
	M50 x 1.5	8	60	<b>0967 710 50</b>	
	M63 x 1.5		75	<b>0967 710 63</b>	

Can be stored in ORSY® system