

ELMO® CLIP



Illustration only



Min./max. temperature resistance	-40 to 80 °C
Colour	Light grey, similar to RAL 7035
Halogen-free	Yes
Silicone-free	Yes

Nominal size	With connection mechanism (vertical)	Elongated hole length	Elongated hole width	Material	Art. No.	P. Qty.
16	Yes	9.4 mm	4.4 mm	PP - Polypropylene	0971 555 016	100
20	Yes	12 mm	4.4 mm	PP - Polypropylene	0971 555 020	100
20	Yes	12 mm	4.4 mm	PP - Polypropylene	0971 555 120	500
25	Yes	12 mm	4.4 mm	PP - Polypropylene	0971 555 025	100
25	Yes	12 mm	4.4 mm	PP - Polypropylene	0971 555 125	400
32	Yes	12 mm	4.4 mm	PP - Polypropylene	0971 555 032	50
40	Yes	12 mm	4.4 cm	PP - Polypropylene	0971 555 040	50
50	No	10.4 mm	5.8 mm	PA - Polyamide	0971 555 050	30
63	No	10.4 mm	5.8 mm	PA - Polyamide	0971 555 063	25

Can be stored in ORSY

Application area

For surface laying of rigid plastic pipes W-IS-EL-F, WPKu-EM-F and WPKu-EM-F-HO

Notice

- EN16-EN40
For nail anchor -Ø 5 mm, can be screwed on M6 stud bolts (e.g. support clip SCZ)
- EN50-EN63
For nail anchor Ø 6 mm

75° Easy-Entry insertion for simple mounting

- Longitudinal hole for lateral alignment during assembly using chipboard screws or nail anchors
- Centre marker for exact alignment of the clips
- EN16-EN40: For inserting in profile rails with 11 mm slot width
- Special side reinforcement for increased break resistance
- Made in Germany



Special side reinforcement for increased break resistance.



Alignment options M 16–M 40.



<STEPREF A="AT_PictureCaption" AR="ASSET_



75° "Easy-Entry insertion" for simple mounting.