

## FLAT WASHER FOR HEXAGON BOLTS AND NUTS

DIN 125 brass, bare

<b>Norms</b>	DIN 125					
<b>Material</b>	Brass					
<b>Surface</b>	Bare					
<b>RoHS-compliant</b>	Yes					

Suitable for screw thread	Internal diameter ( $d_1$ )	Outer diameter ( $d_2$ )	Thickness ( $h_1$ )	Form	Art. No.	P. Qty.
M2	2.2 mm	5 mm	0.3 mm	A	<b>0400 2</b>	10000
M2.5	2.7 mm	6 mm	0.5 mm	B	<b>0400 000 23</b>	1000
M2.6	2.8 mm	7 mm	0.5 mm	A	<b>0400 260</b>	1000
M3	3.2 mm	7 mm	0.5 mm	A	<b>0400 3</b>	300/1000/10000
M3	3.2 mm	7 mm	0.5 mm	B	<b>0400 000 3</b>	1000
M3.5	3.7 mm	8 mm	0.5 mm	A	<b>0400 35</b>	2000
M4	4.3 mm	9 mm	0.8 mm	A	<b>0400 4</b>	300/1000/5000
M4	4.3 mm	9 mm	0.8 mm	B	<b>0400 000 4</b>	1000
M5	5.3 mm	10 mm	1 mm	A	<b>0400 5</b>	300/1000/5000
M5	5.3 mm	10 mm	1 mm	B	<b>0400 000 5</b>	1000
M6	6.4 mm	12 mm	1.6 mm	A	<b>0400 6</b>	300/1000/2500
M6	6.4 mm	12 mm	1.6 mm	B	<b>0400 000 6</b>	1000
M8	8.4 mm	16 mm	1.6 mm	A	<b>0400 8</b>	100/1000
M8	8.4 mm	16 mm	1.6 mm	B	<b>0400 000 8</b>	500
M10	10.5 mm	20 mm	2 mm	A	<b>0400 10</b>	100/500
M10	10.5 mm	20 mm	2 mm	B	<b>0400 000 10</b>	500
M12	13 mm	24 mm	2.5 mm	A	<b>0400 12</b>	100/500
M12	13 mm	24 mm	2.5 mm	B	<b>0400 000 12</b>	500
M14	15 mm	28 mm	2.5 mm	A	<b>0400 14</b>	100/250
M14	15 mm	28 mm	2.5 mm	B	<b>0400 000 14</b>	200
M16	17 mm	30 mm	3 mm	A	<b>0400 16</b>	100/250
M16	17 mm	30 mm	3 mm	B	<b>0400 000 16</b>	200
M18	19 mm	34 mm	3 mm	A	<b>0400 18</b>	500
M18	19 mm	34 mm	3 mm	B	<b>0400 000 18</b>	100
M20	21 mm	37 mm	3 mm	A	<b>0400 20</b>	50/200
M20	21 mm	37 mm	3 mm	B	<b>0400 000 20</b>	100
M24	25 mm	44 mm	4 mm	A	<b>0400 24</b>	100
M24	25 mm	44 mm	4 mm	B	<b>0400 000 24</b>	50
M27	28 mm	28 mm	4 mm	A	<b>0400 27</b>	50
M27	28 mm	50 mm	4 mm	B	<b>0400 000 27</b>	100
M30	31 mm	56 mm	4 mm	B	<b>0400 000 30</b>	50
M36	37 mm	66 mm	5 mm	A	<b>0400 36</b>	25
M36	37 mm	66 mm	5 mm	B	<b>0400 000 36</b>	25
M40	41 mm	72 mm	6 mm	B	<b>0400 000 40</b>	10
M42	43 mm	78 mm	7 mm	B	<b>0400 000 42</b>	25
M45	46 mm	85 mm	7 mm	A	<b>0400 45</b>	25
M45	46 mm	85 mm	7 mm	B	<b>0400 000 45</b>	25
M60	62 mm	62 mm	9 mm	A	<b>0400 60</b>	15

