


SEALING RING ASSORTMENT



Grid dimension

ORSY



DESIGN
AWARD
2017



reddot award 2017
winner



GERMAN
DESIGN
AWARD
WINNER
2018

Art. No.	5964 046 000
P. Qty.	1
Number of pieces in assortment/set	1350 PCS
Material	Copper
DIN	7603
System dimensions	4.4.1

Contents for Art. No.	Designation	Art. No.	Number
5964 046 000	Sealing ring, copper, shape A 6 x 10 mm	0460 6 10	100
	Sealing ring, copper, shape A 8 x 12 mm	0460 8 12	100
	Sealing ring, copper, shape A 8 x 14 mm	0460 8 14	100
	Sealing ring, copper, shape A 10 x 14 mm	0460 10 14	100
	Sealing ring, copper, shape A 10 x 16 mm	0460 10 16	100
	Sealing ring, copper, shape A 12 x 16 mm	0460 12 16	100
	Sealing ring, copper, shape A 12 x 18 mm	0460 12 18	100
	Sealing ring, copper, shape A 14 x 18 mm	0460 14 18	100
	Sealing ring, copper, shape A 14 x 20 mm	0460 14 20	100
	Sealing ring, copper, shape A 16 x 22 mm	0460 16 22	100
	Sealing ring, copper, shape A 18 x 24 mm	0460 18 24	50
	Sealing ring, copper, shape A 20 x 26 mm	0460 20 26	50
	Sealing ring, copper, shape A 22 x 27 mm	0460 22 27	50
	Sealing ring, copper, shape A 24 x 30 mm	0460 24 30	50
	Sealing ring, copper, shape A 26 x 32 mm	0460 26 32	50
	Sealing ring, copper, shape A 28 x 34 mm	0460 28 34	50
	Sealing ring, copper, shape A 30 x 36 mm	0460 30 36	25
	Sealing ring, copper, shape A 32 x 38 mm	0460 32 38	25
	System insert, plastic, 4.4.1	5581 003 010	1
	Plastic partition element for system insert	5581 003 014	15
	System case 4.4.1	5581 020 000	1

**1,350 pieces, in system
case 4.4.1. DIN 7603, shape A,
solid copper.**

**All rings in accordance with
DIN 7603 are flat seals on static
surfaces**

They are used to seal static pipe screw
connections

**Copper rings are corrosion-re-
sistant and can therefore be
used in any environment, except
in the presence of certain strong
acids**

Shape A = flat seal

**Heat-resistant up to max.
+300°C**