


PNEUMATIC FITTINGS



- Connection takes only a few seconds.
- For universal use.
- Closed releasing sleeve prevents interior from becoming soiled.
- Hardened locking pins are wear-resistant.
- Can be used together with steel nipples.
- No corrosion.

Coupling parts made of bare brass. Springs and snap rings are made of stainless steel.
 Operating pressure: 0-70 bar.
 Temperature resistance: -20°C to +100°C.

Storable in [®]ORSY




Quick-Action Couplings

Nominal width 7.2 = 40 mm²


Blocks in one direction
 Female thread

A (connection)	Dia. in mm	L in mm	D in mm	Art. No.	P. Qty.
G 1/4"	22	41	27	0699 101 4	5
G 3/8"	22	41	27	0699 103 8	5
G 1/2"	24	42.5	27	0699 101 2	5




Male thread

A (connection)	Dia. in mm	L in mm	D in mm	Art. No.	P. Qty.
G 1/4"	22	40	27	0699 111 4	5
G 3/8"	22	41	27	0699 113 8	5
G 1/2"	24	41	27	0699 111 2	5



Hose connection


A (connection)	L in mm	D in mm	Art. No.	P. Qty.
6 mm	55	27	0699 126	5
9 mm	55	27	0699 129	5
13 mm	55	27	0699 121 3	5



Double Distributor

Female thread

A (connection)	Dia. in mm	B in mm	L in mm	D in mm	Art. No.	P. Qty.
G 3/8"	22	90.5	67	27	0699 133 8	3
G 1/2"	24	90	69	27	0699 131 2	3



Triple Distributor

Female thread

A (connection)	Dia. in mm	B in mm	L in mm	D in mm	Art. No.	P. Qty.
G 3/8"	22	119	92	27	0699 143 8	3
G 1/2"	24	113	91	27	0699 141 2	3