

WFK VDE CABLE JUNCTION BOXES



- As per DIN EN IEC 60998-2-5
- Application: Protected installations outdoors as per DIN VDE 0100-737, indoors
- Large connection space
- Extremely rugged (impact resistant and ball-proof)
- Plastofast-stainless-steel screws for secure cover seating
- Temperature range: -25°C to +40°C
- Color: similar to RAL 7035 (gray)
- Halogen- and silicone-free
- Material: polystyrene

For demanding requirements and difficult usage conditions.

Type	WFK 1	WFK 2	WFK 3	WFK 4
Appearance				
Cross section in mm ²	up to 2.5	up to 4.0	up to 6.0	up to 10.0
Nominal voltage U _i	690 V	690 V	690 V	690 V
Protection type	IP65	IP65	IP54/IP65	IP54/IP65
Impact resistance	IK07	IK07	IK07	IK07
Dimensions in mm	80 x 80 x 51	93 x 93 x 54	110 x 110 x 64	140 x 140 x 75
Version	Self-sealing, soft membrane inserts, sealing range: 2 - 16 mm		Metric knockouts, scope of delivery: IP54 connections and sealing plugs, M25, sealing range: 9 - 18.5 mm	Metric knockouts, scope of delivery: IP54 connections and sealing plugs, M32, sealing range: 13 - 23 mm
Inserts				
Empty Art. No.	0975 050 110	0975 050 120	0975 050 130	0975 050 140
With raised screw terminal, 5-pins Art. No.	-	-	0975 050 131	0975 050 141
Empty, with external connection tabs Art. No.	0975 050 112	0975 050 122	-	-
Empty, with red cover Art. No.	0975 050 113	0975 050 123	-	-
P. Qty.	3	3	2	2

Additional articles:
Cable Glands, IP 68, metric, polyamide
 Art. No. 0967 705 ...
Locking Nuts, metric, polyamide
 Art. No. 0967 710 ...