

# ASSY® 3.0 SK

# ASSY®

| d<br>in mm | l<br>in mm | lg<br>in mm | dh<br>in mm | End mill | Drive | Art. No.<br>galvanized,<br>yellow | P. Qty. |
|------------|------------|-------------|-------------|----------|-------|-----------------------------------|---------|
| 8,0        | 220        | 100         | 22,0        | x        | AW®40 | 0184 808 220                      | 50      |
|            | 240        |             |             | x        |       | 0184 808 240                      |         |
|            | 260        |             |             | x        |       | 0184 808 260                      |         |
|            | 280        |             |             | x        |       | 0184 808 280                      |         |
|            | 300        |             |             | x        |       | 0184 808 300                      |         |
|            | 320        |             |             | x        |       | 0184 808 320                      |         |
|            | 340        |             |             | x        |       | 0184 808 340                      |         |
|            | 360        |             |             | x        |       | 0184 808 360                      |         |
|            | 380        |             |             | x        |       | 0184 808 380                      |         |
|            | 400        |             |             | x        |       | 0184 808 400                      |         |
|            | 420        |             |             | x        |       | 0184 808 420                      |         |
|            | 440        |             |             | x        |       | 0184 808 440                      |         |
|            | 460*       |             |             | x        |       | 0184 808 460                      |         |
|            | 480*       |             |             | x        |       | 0184 808 480                      |         |
|            | 500*       |             |             | x        |       | 0184 808 500                      |         |
| 10,0       | 100        | 60          | 25,0        | x        | AW®50 | 0184 810 100                      | 50      |
|            | 120        | 80          |             | x        |       | 0184 810 120                      |         |
|            | 140        |             |             | x        |       | 0184 810 140                      |         |
|            | 160        |             |             | x        |       | 0184 810 160                      |         |
|            | 180        | 100         |             | x        |       | 0184 810 180                      |         |
|            | 200        |             |             | x        |       | 0184 810 200                      |         |
|            | 220        |             |             | x        |       | 0184 810 220                      |         |
|            | 240        |             |             | x        |       | 0184 810 240                      |         |
|            | 260        |             |             | x        |       | 0184 810 260                      |         |
|            | 280        |             |             | x        |       | 0184 810 280                      |         |
|            | 300        |             |             | x        |       | 0184 810 300                      |         |
|            | 320        | 120         |             | x        |       | 0184 810 320                      |         |
|            | 340        |             |             | x        |       | 0184 810 340                      |         |
|            | 360        |             |             | x        |       | 0184 810 360                      |         |
|            | 380        |             |             | x        |       | 0184 810 380                      |         |
|            | 400        |             |             | x        |       | 0184 810 400                      |         |
|            | 420        |             |             | x        |       | 0184 810 420                      |         |
|            | 440        |             |             | x        |       | 0184 810 440                      |         |
|            | 460        |             |             | x        |       | 0184 810 460                      |         |
|            | 480        |             |             | x        |       | 0184 810 480                      |         |
|            | 500        |             |             | x        |       | 0184 810 500                      |         |
| 12,0       | 200        | 100         | 29,0        | x        | AW®50 | 0184 812 200                      | 50      |
|            | 120        | 120         |             | x        |       | 0184 812 220                      |         |
|            | 240        |             |             | x        |       | 0184 812 240                      |         |
|            | 260        |             |             | x        |       | 0184 812 260                      |         |
|            | 280        |             |             | x        |       | 0184 812 280                      |         |
|            | 300        |             |             | x        |       | 0184 812 300                      |         |
|            | 320        |             |             | x        |       | 0184 812 320                      |         |
|            | 340        |             |             | x        |       | 0184 812 340                      |         |
|            | 360        |             |             | x        |       | 0184 812 360                      |         |
|            | 380        | 145         |             | x        |       | 0184 812 380                      |         |
|            | 400        |             |             | x        |       | 0184 812 400                      |         |
|            | 440        |             |             | x        |       | 0184 812 440                      |         |
|            | 480        |             |             | x        |       | 0184 812 480                      |         |
|            | 520        |             |             | x        |       | 0184 812 520                      |         |

## Note:

Do not use the screw in applications exposed directly to the elements, in humid rooms and in atmospheres containing chlorine gas. For applications outdoors and in rooms which are briefly or constantly subjected to high humidity, please use the stainless-steel screw ASSY® 3.0 SK A2 in this case.



ETA-11/0190

\*) Not approved as per ETA 11/0190 or ABZ. No CE marking.

Storable in ORSY®

**ASSY® 3.0** particle board screws are optimized for use in wooden materials. When used in plastic anchors, a reduction of the load-bearing capacity is possible. For this reason, we recommend only using screws without optimized thread tips (drilling tip, counter thread, ring thread, ground corrugated, self-clearing groove etc.), e.g. anchor screws, Pre. No. 0157, hex. wood screws DIN 571, Pre. No. 0192, Wüpfast® screws, Pre. No. 0186, 0198).