

CABLE CONNECTOR, NON-INSULATED

AMP MCP contact 1.5							
Plug-in connector systems, 1.5 mm, with symmetrical locking lugs, * for single-wire seals							
Appearance	in mm ²	Seal dia. in mm	Plug in mm	Material	Surface	Art. No.	P. Qty.
	0.2 - 0.35	-	1.6 x 0.6	CuNiSi	Sn (tinned)	0558 197 001	100
		2.60				0558 197 004*	
	0.5 - 1.0	-			Sn (tinned)	0558 197 002	
		2.60				0558 197 005*	
		-			Sn (tinned) silver-plated	0558 197 012	50
		2.60				0558 197 015*	

Storable in [®]ORSY

Additional products - recommended:

Releasing tool **Art. No. 0713 558,321**
 Single-wire seals **Art. No. 0558 991 403**

AMP MCP contact 2.8								
Plug-in connector systems, 2.8 mm, with symmetrical locking lugs, * for single-wire seals								
Appearance	in mm ²	Seal dia. in mm	Plug in mm	Material	Surface	Art. No.	P. Qty.	
	0.2 - 0.35	-	2.8 x 0.8	CuNiSi	Sn (tinned)	0558 198 001	50	
		3.40				0558 198 005*		
		0.5 - 1.0			-	Sn (tinned) silver-plated		0558 198 011
					3.40			0558 198 015*
	Sn (tinned)				0558 198 002			
					0558 198 006*			
	Sn (tinned) silver-plated				0558 198 012			
					0558 198 016*			
	1.5 - 2.5				-	Sn (tinned)		0558 198 003
					3.40			0558 198 007*
		-			Sn (tinned) silver-plated	0558 198 013		
		3.40				0558 198 017*		

Storable in [®]ORSY

Additional products - recommended:

Releasing tool **Art. No. 0713 558,322**
 Single-wire seals **Art. No. 0558 991 4...**

AMP Micro Power Quadlok Contact/Flat Plug 2.8							
Plug-in connector systems, 2.8 mm, with one locking lug							
Appearance	in mm ²	Plug in mm	Material	Surface	Art. No.	P. Qty.	
	0.5 - 1.0	2.8 x 0.63	CuNiSi/CuSn	Sn (tinned)	0558 190 101	100	
	1.5 - 2.5				0558 190 102		
	0.5 - 1.0		CuSn		0558 191 101		
	1.5 - 2.5				0558 191 102		

Storable in [®]ORSY

Additional products - recommended:

Releasing tool **Art. No. 0713 558,212**