

## LOCKING SCREWS

metric EN 60423

Material	Brass, nickel-plated
Temperature range	Up to +200°C
Protection type	IP54

	Connection thread	Head dia. in mm	Thread length in mm	Art. No.	P. Qty.
	M12 x 1.5	16	5	<b>0967 775 12</b>	100
	M16 x 1.5	20	6	<b>0967 775 16</b>	100
	M20 x 1.5	24	6.5	<b>0967 775 20</b>	100
	M25 x 1.5	28	7	<b>0967 775 25</b>	50
	M32 x 1.5	35	8	<b>0967 775 32</b>	50
	M40 x 1.5	45	8	<b>0967 775 40</b>	50
	M50 x 1.5	55	9	<b>0967 775 50</b>	50
	M63 x 1.5	68	10	<b>0967 775 63</b>	10

## REDUCERS

metric EN 60423

Material	Brass, nickel-plated
Temperature range	Up to +200°C

	Connection thread from	Connection thread to	Outside dia. in mm	Thread length in mm	Height in mm	Art. No.	P. Qty.
	M16 x 1.5	M12 x 1.5	20	6	8.5	<b>0967 781 612</b>	100
	M20 x 1.5	M12 x 1.5	24	6.5	9	<b>0967 782 012</b>	100
	M20 x 1.5	M16 x 1.5	24	6.5	9	<b>0967 782 016</b>	100
	M25 x 1.5	M16 x 1.5	30	7	10	<b>0967 782 516</b>	100
	M25 x 1.5	M20 x 1.5	30	7	10	<b>0967 782 520</b>	100
	M32 x 1.5	M20 x 1.5	39	8	11.5	<b>0967 783 220</b>	50
	M32 x 1.5	M25 x 1.5	39	8	11.5	<b>0967 783 225</b>	25
	M40 x 1.5	M25 x 1.5	50	9	12.5	<b>0967 784 025</b>	25
	M40 x 1.5	M32 x 1.5	50	9	12.5	<b>0967 784 032</b>	25
	M50 x 1.5	M32 x 1.5	57	10	14	<b>0967 785 032</b>	10
	M50 x 1.5	M40 x 1.5	57	10	14	<b>0967 785 040</b>	10
	M63 x 1.5	M40 x 1.5	70	10	14	<b>0967 786 340</b>	5
	M63 x 1.5	M50 x 1.5	70	10	14	<b>0967 786 350</b>	5

## EXTENSIONS

metric EN 60423

Material	Brass, nickel-plated
Temperature range	Up to +200°C

	Connection thread from	Connection thread to	Height in mm	Thread length in mm	Width across flats in mm	Art. No.	P. Qty.
	M12 x 1.5	M16 x 1.5	16	5	18	<b>0967 788 12</b>	100
	M16 x 1.5	M20 x 1.5	16.5	5	22	<b>0967 788 16</b>	100
	M20 x 1.5	M25 x 1.5	18.5	6	27	<b>0967 788 20</b>	50
	M25 x 1.5	M32 x 1.5	20.5	7	34	<b>0967 788 25</b>	25
	M32 x 1.5	M40 x 1.5	23.5	8	42	<b>0967 788 32</b>	10
	M40 x 1.5	M50 x 1.5	30	8	52	<b>0967 788 40</b>	5
	M50 x 1.5	M63 x 1.5	32.5	9	65	<b>0967 788 50</b>	5