

ELMO® KAW CABLE UNWINDER



Side guide



Long tapered roll-up surfaces

Light aluminum design

Long tapered roll-up surfaces

- Easier rolling up and positioning of cable drum
- Reduced loading for rollers when placing cable drum

Side guide

Prevents accidental slipping off of cable drum


Optimum adjustment to respective cable drum size

Rollers can be adjusted in 8 different positions using spring lock

Slip-proof contact surface

Art. No.	0975 811 001	0975 811 002
P. Qty.	1	1
Model designation	KAW 3	KAW 4
Min./max. diameter	200 - 700 mm	200 - 700 mm
Length	700 mm	700 mm
Width	515 mm	670 mm
Height	100 mm	100 mm
Load-bearing capacity	200 kg	250 kg
Weight	8.6 kg	10.3 kg
Material	Aluminum	Aluminum
Color	Aluminum colors	Aluminum colors

CABLE UNWINDER KAW 1



Ball-bearing rollers, adjustable with spring lock

Roller spacing:

- Position 1: 150 mm
- Position 2: 300 mm

Easy rolling up and positioning of cable drum

with inclined roll-up surface

Slip-proof contact surface

Art. No.	0975 810 1
P. Qty.	1
Length	530 mm
Width	550 mm
Height	100 mm
Load-bearing capacity	120 kg
Surface	PLV Powder-coated Powder-coated
Color	Traffic red RAL 3020 RAL 3020 Traffic red RAL 3020