

SYNTHETIC CORUNDUM FLAP WHEELS

Material of abrasive medium	Aluminium oxide
Material to be processed	C-steel, Grey cast iron, Forged steel, Steels bands, Cr-Ni and other stainless steels, Non-ferrous metal, Deep-drawn steel, Cast metal, Malleable cast iron, Injection-moulded zinc, Stainless steel

Diameter x width x shaft diameter	Grid size	Recommended rotation speed	Max. rotation speed	Art. No.	P. Qty.
80 x 50 x 6 mm	120	4800 U/min(rpm)	9500 U/min(rpm)	0672 010 851	5
80 x 50 x 6 mm	150	4800 U/min(rpm)	9500 U/min(rpm)	0672 010 855	5
80 x 50 x 6 mm	240	4800 U/min(rpm)	9500 U/min(rpm)	0672 010 857	5
80 x 50 x 6 mm	320	4800 U/min(rpm)	9500 U/min(rpm)	0672 010 859	5

Related products	Art. No.
Collet chuck for straight grinder 3 mm	0702 520 001
Collet chuck for straight grinder 6 mm	0702 520 002
Collet chuck for straight grinder 8 mm	0702 520 003
Clamping frame for straight grinder	0702 520 004
Flexible shaft for straight grinder	0702 520 005
Collet chuck for flexible shaft 3 mm	0702 520 006
Collet chuck for flexible shaft 6 mm	0702 520 007
Collet chuck for flexible shaft 8 mm	0702 520 008
Clamp for clamping frame	0702 520 009