

HEAT-SHRINK CRIMP RING CONNECTOR



Illustration only

Semi-transparent heat-shrink tubing

Straightforward visual monitoring of the connection

40% quicker shrinking behaviour

Time-saving

Low shrinking temperature of +100 °C

Low risk of damage for connector and cable insulation

Dielectric strength	30 kV/mm
IP protection class	IP 67
Min./max. temperature conditions	-55 to 125 °C
Min. shrinkage temperature	300 °C

Min./max. wire cross section	Colour	Flange hole	Art. No.	P. Qty.
0.5-1.5 mm ²	Red	M4	0555 511 104	50 / 100
0.5-1.5 mm ²	Red	M5	0555 511 105	50 / 100
0.5-1.5 mm ²	Red	M6	0555 511 106	50 / 100
0.5-1.5 mm ²	Red	M8	0555 511 108	50 / 100
0.5-1.5 mm ²	Red	M10	0555 511 110	50
1.5-2.5 mm ²	Blue	M4	0555 511 204	50 / 100
1.5-2.5 mm ²	Blue	M5	0555 511 205	50 / 100
1.5-2.5 mm ²	Blue	M6	0555 511 206	50 / 100
1.5-2.5 mm ²	Blue	M8	0555 511 208	50 / 100
1.5-2.5 mm ²	Blue	M10	0555 511 210	50
4-6 mm ²	Yellow	M4	0555 511 404	50
4-6 mm ²	Yellow	M5	0555 511 405	50
4-6 mm ²	Yellow	M6	0555 511 406	50
4-6 mm ²	Yellow	M8	0555 511 408	50
4-6 mm ²	Yellow	M10	0555 511 410	50

Can be stored in ORSY

Application area

Dust-proof and damp-proof connections.

Good to excellent resistance against petrol, battery acid, diesel, engine oil, anti-freeze, brake fluid, 5% saline solution, isopropyl alcohol.

Proof of Performance

RoHS-compliant

Notice

Avoid localised overheating of the heat-shrink tubing.