

W-FAZ/S FIXING ANCHOR

02.5

Anchor dimensions: W-FAZ/S Fixing Anchor, galvanized steel



Description	Anchor dia.	Standard anchoring depth			Reduced anchoring depth			Overall length L [mm]	Wrench size [mm]	Approval ETA	Art. No.	P. Qty.						
		Attachment height t _{fix} [mm]	Drill hole dia. x depth [mm]	Effective anchoring depth h _{ef} [mm]	Attachment height t _{fix} [mm]	Drill hole dia. x depth [mm]	Effective anchoring depth h _{ef} [mm]											
W-FAZ/S	M8	-	-	-	11	8 x 49	35	65	13	ETA-99/0011	5928 258 011	100						
		10	8 x 60	46	21			75			5928 208 010	100						
		15			26			80			5928 208 015	100						
		30			41			95			5928 208 030	100						
		50			61			115			5928 208 050	100						
		100			111			165			5928 208 100	50						
	M10	-			-	-	10	10 x 55	40		70	17	5928 251 010	50				
		-	-	-	20	80	5928 251 020				50							
		10	10 x 75	60	30	90	5928 210 010				50							
		15			35	95	5928 210 015				50							
		20			40	100	5928 210 020				50							
		30			50	110	5928 210 030				50							
		50			70	130	5928 210 050				50							
		75			95	155	5928 210 075				50							
		100			120	180	5928 210 100				50							
		150			-	-	230				0904 521 005		25					
		M12			-	-	-				10		12 x 70	50	85	19	5928 252 010	25
					-	-	-				20				95		5928 252 020	25
					15	12 x 90	70				35				110		5928 212 015	25
					20						40				115		5928 212 020	25
	30				50			125	5928 212 030		25							
	50				70			145	5928 212 050		25							
	65		85	160	5928 212 065			25										
	85		105	180	5928 212 085			25										
	105		125	200	5928 212 105			25										
	125		-	-	220			0904 521 217	25									
	145		-	-	240			0904 521 218	20									
	160		-	-	255			0904 521 219	20									
	M16		-	-	-			15	16 x 90		65	115			24		5928 256 015	20
			5	16 x 110	85			25				125					5928 216 005	20
		15	35					135				5928 216 015	20					
		25	45					145				5928 216 025	20					
		50	70			170	5928 216 050	20										
		80	100			200	5928 216 080	10										
		100	-			-	220	0904 521 603				10						
		140	-			-	260	0904 521 604				10						
		180	-			-	300	0904 521 605				10						
		M20	30			20 x 125	100	-				-	-	165		30	5928 220 030	10
	60		-					-	-		195	5928 220 060	10					
	130		-	-	-			265	0904 522 003		5							
	150		-	-	-			285	0904 522 004		5							
	M24	30	24 x 145	115	-	-	-	190	36		0904 522 401	10						
		60			-	-	-	220			0904 522 402	5						
		75			-	-	-	235			0904 522 403	5						
		100			-	-	-	260			0904 522 404*	5						
	M27	30	28 x 160	125	-	-	-	210	41		0904 522 701*	5						
		60			-	-	-	240			0904 522 702*	5						
		100			-	-	-	280			0904 522 703*	5						

* S-24 cannot be ordered.