

# **FLUSH-MOUNTED FIXING CLIP**





Art. No.	0971 300 900
P. Qty.	100
Min./max. slot width	30-60 mm
Length (a)	60 mm
Height (c)	38 mm
Min./max. temperature resistance	-40 to 85 °C
Colour	White
Material	Polyoxymethylene
Halogen-free	Yes
Silicone-free	Yes

Compatible with ORSY® storage system

## Rapid and tool-free cable attachment in masonry slots up to 60 mm

- High clamping force
- No showing through plaster thanks to neutral colour
- No damage to lines possible
- Easy assembly thanks to finger eyelet
- Greatly reduced assembly time
  - 50% time saving

#### **Application area**

Pipe/cable laying in masonry slots

# **FLUSH-MOUNTED FIXING CLAMP**







### Rapid and tool-free pipe attachment in masonry slots up to 45 mm wide

- High clamping force
- Does not show through plaster
- No damage to the pipes
- Simple installation
- Assembly time is significantly reduced - time savings of 50%

### **Application area**

Pipe/cable laying in masonry slots

Art. No.	0971 300 910
P. Qty.	200
Min./max. slot width	12-45 mm
Length (a)	60 mm
Height (c)	45 mm
Min./max. temperature resistance	-20 to 75 °C
Colour	Light grey, similar to RAL 7035
Material	PA - Polyamide
Halogen-free	Yes
Silicone-free	Yes