

## BRAIDED HOSE



Illustration only



**Can be cut cold – no fraying, no special tool required**

- Lines are easy to bundle
- Good protection against abrasion

### Application area

Used to protect or bundle cables, lines, wires and hoses in cable fabrication, the automotive and electrical industries and switch and system construction

<b>Colour</b>	Black
<b>Min./max. temperature resistance</b>	-55 to 125 °C
<b>Flammability</b>	Self-extinguishing as per UL94
<b>Material</b>	PA - Polyamide
<b>Halogen-free</b>	Yes

Min./max. diameter	Art. No.	P. Qty.
4-10 mm	<b>0771 500 030</b>	20
10-14 mm	<b>0771 490 012</b>	15
14-24 mm	<b>0771 480 016</b>	15
18-26 mm	<b>0771 470 020</b>	10
26-36 mm	<b>0771 460 030</b>	10
32-44 mm	<b>0771 450 040</b>	5

## FABRIC SHRINK HOSE



Illustration only



**Shrink rate 2:1**

### Tight and flexible

Perfect protection even for tight radii

### Very good heat protector/insulator

### Excellent protection against abrasion and rodents

### Excellent chemical resistance

### Application area

Used to protect or bundle cables, lines, wires and hoses in cable fabrication, the automotive and electrical industries and switch and system construction

<b>Colour</b>	Black
<b>Min./max. temperature resistance</b>	-40 to 150 °C
<b>Flammability</b>	Self-extinguishing as per UL94 HB
<b>Material</b>	PES - Polyester
<b>Halogen-free</b>	Yes

Diameter	Diameter (shrunk)	Art. No.	P. Qty.
12 mm	6 mm	<b>0771 550 012</b>	5
25.0 mm	12.0 mm	<b>0771 560 025</b>	5
30.0 mm	15.0 mm	<b>0771 570 030</b>	5
50.0 mm	25.0 mm	<b>0771 590 050</b>	4
70.0 mm	35.0 mm	<b>0771 610 070</b>	4