

LIGHT METAL SPIRIT LEVEL



Art. No.	0714 644 125
P. Qty.	1
Length (L)	25 cm
Height (H)	20 mm
Width (B)	50 mm
Number of magnets	2 PCS
Measuring accuracy (per length)	0.5 mm/m
Measuring accuracy for overhead measurements (per length)	0.75 mm/m
Degrees measuring accuracy	0.029 degree
Degrees measuring accuracy for overhead measurements	0.043 Degree

Rugged light metal spirit level for metalworking and construction trades

Excellent reading and simple determination of gradients

Six-line level for 1% and 2% gradients

Direct testing of gradients

360° rotating angle level with scaling

No liquid discolouration, maximum precision with fluctuating temperatures

Fluorescent level liquid, highly-resistant to UV radiation

Extra-strong hold on pipes, profiles and steel components

Milled measuring surface with V-shaped groove and rare earth magnets

For the toughest applications

Extra-strong die-cast aluminium profile

SMALL SPIRIT LEVEL, ELECTRIC



Art. No.	0714 644 510
P. Qty.	1
Length (L)	67 mm
Height (H)	18 mm
Width (B)	41 mm
Number of magnets	1 PCS
Measuring accuracy (per length)	1 mm/m
Measuring accuracy for overhead measurements (per length)	1 mm/m

Spirit level for aligning switches and sockets

Very strong hold on metallic surfaces

Extra-strong rare earth magnet

Excellent reading and long service life

Level block made from acrylic glass with inlaid, corrosion-free reading rings

No liquid discolouration, maximum precision with fluctuating temperatures

Fluorescent level liquid, highly resistant to UV radiation

Application as standard spirit level

Additional ground measuring surface