

## CABLE GLAND

Metric EN 60423 / EN 62444

<b>Material</b>	<b>Polyamide PA6 V-2</b> , halogen and silicone-free
Sealing ring	Polychloroprene nitrile rubber CR/NBR, halogenic
Temperature range	-20°C to +100°C
Protection rating	IP68 - 5 bar
Colour	Jet black RAL 9005



	Threaded connection	Cable dia. mm (clamping range)	Thread length mm	Width across flats mm	Art. no.	PU qty.
	M12 x 1.5	3-6	8	15	<b>0967 706 012</b>	100
	M16 x 1.5	5-10		20	<b>0967 706 016</b>	
	M20 x 1.5	8-13		24	<b>0967 706 020</b>	
	M25 x 1.5	11-17		29	<b>0967 706 025</b>	
	M32 x 1.5	15-21	10	36	<b>0967 706 032</b>	25
	M40 x 1.5	19-28		46	<b>0967 706 040</b>	10
	M50 x 1.5	27-35	12	55	<b>0967 706 050</b>	5
	M63 x 1.5	32-42		68	<b>0967 706 063</b>	

Can be stored in ORSY® system

## COUNTER NUT

Metric EN 60423

<b>Material</b>	<b>Polyamide PA6 GF30</b> , halogen and silicone-free
Temperature range	-20°C to +100°C
Colour	Jet black RAL 9005

	Threaded connection	Thread length mm	Width across flats mm	Art. no.	PU qty.
	M12 x 1.5	5	17	<b>0967 712 12</b>	100
	M16 x 1.5		22	<b>0967 712 16</b>	
	M20 x 1.5	6	27	<b>0967 712 20</b>	
	M25 x 1.5		32	<b>0967 712 25</b>	
	M32 x 1.5	7	41	<b>0967 712 32</b>	50
	M40 x 1.5		50	<b>0967 712 40</b>	
	M50 x 1.5	8	60	<b>0967 712 50</b>	
	M63 x 1.5		75	<b>0967 712 63</b>	

Can be stored in ORSY® system