

SET SCREWS

DIN EN ISO 4028

replaces DIN 915

with Allen socket and stud

A2 stainless steel, 21 H
A4 stainless steel, 21 H



Hardness 21H corresponds to a hardness of 210 HV.

Nominal dia. d	Length l in mm	A2 stainless steel Art. No.	P. Qty.	A4 stainless steel Art. No.	P. Qty.
M8	8	0222 8 8	100	0266 8 8	100
	10	0222 8 10		0266 8 10	
	12	0222 8 12		0266 8 12	
	14	0222 8 14			
	16	0222 8 16		0266 8 16	
	20	0222 8 20		0266 8 20	
	25	0222 8 25		0266 8 25	
	30	0222 8 30		0266 8 30	
	35	0222 8 35		0266 8 35	
	40	0222 8 40		0266 8 40	
	45	0222 8 45			
	50	0222 8 50			
M10	10	0222 10 10	100		100
	12	0222 10 12		0266 10 12	
	16	0222 10 16		0266 10 16	
	20	0222 10 20		0266 10 20	
	25	0222 10 25		0266 10 25	
	30	0222 10 30		0266 10 30	
	35	0222 10 35			
	40	0222 10 40		0266 10 40	
	45	0222 10 45			
	50	0222 10 50			
	60	0222 10 60			
M12	12	0222 12 12	100		50
	14	0222 12 14			
	16	0222 12 16			
	20	0222 12 20		0266 12 20	
	25	0222 12 25			
	30	0222 12 30		0266 12 30	
	35	0222 12 35			
	40	0222 12 40	50	0266 12 40	
	45	0222 12 45			
	50	0222 12 50			

Can be stored in ORSY®

DIN 915 has been retracted and replaced by international standard DIN EN ISO 4028.