

WATERPROOF SOCKET HOUSING

TE Superseal 1.5 Series

Proof of Performance

Complies with IEC 529 and DIN 40050
IP 67



Illustration only

Art. No.	0555 103 1	0555 103 2	0555 103 3	0555 103 4	0555 103 5	0555 103 6
P. Qty.	4/10	4/10	4/10	4/10	4/10	4/10
Number of electrical poles	1 PCS	2 PCS	3 PCS	4 PCS	5 PCS	6 PCS
Contact gauge	1.5 mm					
Min./max. wire cross section	0.35-2.5 mm ²					
IP protection class	IP 67					
Max. nominal voltage	24 V/DC					
Max. current	14 A					
Min./max. temperature conditions	-40 to 125 °C					
Material	PA - Polyamide					
Colour	Black	Black	Black	Black	Black	Black

Compatible with ORSY® storage system

Related products	Art. No.
Single wire seal (SEAL) 1.2-2.1 mm; Orange	0558 991 406
Single wire seal (SEAL) 1.7-2.4 mm; Yellow	0558 991 41
Single wire seal (SEAL) 2.5-3.3 mm; Red	0558 991 42
Sealing stoppers	0558 991 45
Flat connector contact MINI MIC SRS 1.5 0.35-0.5 mm ²	0558 995 80
Flat connector contact MINI MIC SRS 1.5 0.75-1.5 mm ²	0558 995 82
Flat connector contact MINI MIC SRS 1.5 1.5-2.5 mm ²	0558 995 84
Removal tool	0713 558 241
Crimping pliers With integrated locator 0.35-1.5 mm ²	0714 107 130

Application area

Car, lorry, construction/agricultural machinery, motorbikes, boat building etc.