

TWO-HAND ANGLE GRINDER



ANTI-VIBRATION SYSTEM



Quick-action nut only included in scope of delivery for EWS 24-180-S and EWS 24-230-S.

Delivery scope					
Designation	EWS 24-180 Art. No.	EWS 24-180-S Art. No.	EWS 24-230 Art. No.	EWS 24-230-S Art. No.	P. Qty.
Two-Hand Angle Grinder	0702 445 X		0702 446 X		1
Protective Hood with quick adjustment	0708 445 032		0708 446 002		1
Anti-Vibration Handle	0708 445 001				1
Bottom Flange	0708 414 032				1
Clamping Nut	0708 486 033	-	0708 486 033	-	1
Face Wrench	0702 489 904	-	0702 489 904	-	1
Quick-Action Nut	-	0702 489 900	-	0702 489 900	1

Technical data			
Designation		EWS 24-180/-S	EWS 24-230/-S
Voltage	V/Hz	230/50	
Protection class		□/II	
Power consumption	in W	2,400	
Output	in W	1,600	
Idling speed	in rpm	8,500	6,600
Max. wheel diameter	in mm	180	230
Spindle thread	M	14	
Cable length	in m	4	
Weight	in kg	5.7	5.8

2,400 W angle grinders with vibration damping and a rotating handle.

EWS 24-180
(without quick-action nut)
Art. No. 0702 445 10

EWS 24-180-S
(with quick-action nut)
Art. No. 0702 445 20

EWS 24-230
(without quick-action nut)
Art. No. 0702 446 10

EWS 24-230-S
(with quick-action nut)
Art. No. 0702 446 20

Handle can be rotated in 90° increments.

Optimum working position, both when grinding and cutting.

Vibration damping on both handles.

Less fatigue while working.

Soft-start, accidental start-up safeguard, overload indicator.

Increased safety and convenience while working.

Anti-twist protective hood.

The hood cannot be twisted when working and offers optimum protection for the user.

Kick-back guard.

If the wheel suddenly jams, the power supply to the motor is interrupted, considerably reducing the danger of injury.

Overload indicator.

To prevent motor damage, an LED illuminates if the unit becomes overloaded.

3-year warranty.

On manufacturing and material defects.

Empty Carrying Case for angle grinders
Dia. 180 - 230 mm
Art. No. 0955 702 496