

## 15-PIN REPAIR SOCKET EASY 24 V



<b>Art. No.</b>	<b>0510 950 269</b>
<b>P. Qty.</b>	1
<b>Suitable for cable diameter</b>	18 mm
<b>Contact design</b>	Screw contact
<b>Design</b>	Lamellar cap
<b>Contact material</b>	Copper alloy
<b>ISO</b>	12098    Road vehicles - Connectors for the electrical connection of towing and towed vehicles - 15-pole connector for vehicles with 24 V nominal supply voltage

### Quick and easy installation

Contacts feature screw-type connection for easy attachment and release

### No risk of interchanging

No additional instructions needed thanks to marking with standardized cable colors

### Contact insert as complete component

- No loss of individual contacts
- No special tools needed for assembly and removal

## 15-PIN REPAIR SOCKET EASY 24 V



<b>Art. No.</b>	<b>0510 950 219</b>
<b>P. Qty.</b>	1
<b>Suitable for cable diameter</b>	18 mm
<b>Contact design</b>	Screw contact
<b>Design</b>	Lamellar cap
<b>Contact material</b>	Copper alloy
<b>ISO</b>	12098    Road vehicles - Connectors for the electrical connection of towing and towed vehicles - 15-pole connector for vehicles with 24 V nominal supply voltage

### Quick and easy installation

Contacts feature screw-type connection for easy attachment and release

### No risk of interchanging

No additional instructions needed thanks to marking with standardized cable colors

### Contact insert as complete component

- No loss of individual contacts
- No special tools needed for assembly and removal

Supplement to Art. No.:	Designation	Art. No.
0510 950 219	15-pin repair socket, standard 24 V	<b>0510 950 269</b>
	Wire end ferrule without plastic sleeve	<b>0557 175 928</b>
		<b>0557 184 191</b>
	Crimping pliers	<b>0714 107 100</b>
	Wire stripping pliers	<b>0714 108 10</b>
	FLRYY 111 Y Flexible sheathed cable	<b>0770 118 015</b>
	Silicone spray grease	<b>0893 223</b>
Contact OL	<b>0893 60</b>	